

MRCOOL

Olympus Hyper Heat Series

Ductless Mini-Split Heat Pump A/C

Enhanced Performance



Superior Heating
Saves you money
Supreme efficiency
Low ambient cooling



Version Date: 05-18-2022

Best Features



Leakage Detection



Follow Me®



Gold Fin® Condenser



Smartphone App



Enhanced Heating



Quiet Running



DC Inverter

Specification

| Model No. | Indoor Unit | 0-09-HP-WMAH-230A | 0-12-HP-WMAH-230A | 0-18-HP-WMAH-230A | 0-24-HP-WMAH-230A |
|-----------|--------------|-------------------|-------------------|-------------------|-------------------|
| | Outdoor Unit | 0-HH-09-HP-C-230 | 0-HH-12-HP-C-230 | 0-HH-18-HP-C-230 | 0-HH-24-HP-C-230 |

Capacity & Performance

| | | | | | |
|-------------------------------|-------|--------------|--------------|--------------|--------------|
| Cooling Capacity | Btu/h | 9000 | 12000 | 17000 | 24000 |
| SEER | Btu/W | 25.0 | 22.5 | 20.0 | 20.5 |
| Heating Capacity | Btu/h | 10900 | 12000 | 18000 | 29000 |
| HSPF | | 11.2 | 12 | 10.3 | 11.5 |
| Indoor noise level (Hi/Mi/Lo) | dB(A) | 38/33.5/23.5 | 38/33.5/23.5 | 45.5/36/29.5 | 48.5/44/38.5 |
| Outdoor noise level () | dB(A) | 55.5 | 56 | 57.5 | 60 |

Electrical Parts

| | | | | | |
|------------------------------|---------|---------------------|---------------------|---------------------|---------------------|
| Power Supply | Ph-V-Hz | 208-230V~ 60Hz, 1Ph | 208-230V~ 60Hz, 1Ph | 208-230V~ 60Hz, 1Ph | 208-230V~ 60Hz, 1Ph |
| Minimum Circuit (Disconnect) | A | 9.0 | 9.0 | 18.0 | 20.0 |
| Maximum Fuse (Breaker) | A | 15.0 | 15.0 | 25.0 | 30.0 |

Dimensions & Weight

| | | | | | | |
|-------------------|---------|------|-----------------------|-----------------------|-----------------------|------------------------|
| Net Dimension | Indoor | inch | 32.87 x 7.80 x 11.02 | 32.87 x 7.80 x 11.02 | 38.98 x 8.58 x 12.40 | 46.69 x 10.16 x 13.50 |
| | Outdoor | inch | 31.50x13.11x21.81 | 31.50 x 13.11 x 21.81 | 33.27 x 14.29 x 27.64 | 37.24 x 16.14 x 31.89 |
| Packing Dimension | Indoor | inch | 35.83 x 10.63 x 13.98 | 35.83 x 10.63 x 13.98 | 41.93 x 11.81 x 15.75 | 49.80 x 16.54 x 14.17 |
| | Outdoor | inch | 36.22 x 15.35 x 24.61 | 36.22 x 15.35 x 24.61 | 37.99 x 15.55 x 30.12 | 42.91 x 19.69 x 34.456 |
| Net weight | Indoor | lbs | 18.52 | 18.52 | 25.13 | 37.70 |
| | Outdoor | lbs | 88.18 | 88.18 | 108.47 | 138.89 |
| Gross Weight | Indoor | lbs | 25.35 | 25.35 | 34.17 | 44.09 |
| | Outdoor | lbs | 93.7 | 93.7 | 115.52 | 151.02 |

Refrigerant & Piping

| | | | | | |
|-----------------------------|------|------------|------------|------------|------------|
| †Refrigerant R410A | oz | R410A/52.9 | R410A/52.9 | R410A/68.8 | R410A/91.7 |
| Piping Size Liquid/Gas side | inch | 1/4"-3/8" | 1/4"-1/2" | 1/4"-1/2" | 3/8"-5/8" |

National Average Annual Operating Costs

| | | | | | |
|---------------|----|-----|-----|-----|-----|
| Cooling Cost* | \$ | 45 | 67 | 107 | 148 |
| Heating Cost* | \$ | 196 | 198 | 353 | 421 |

* Data provided by AHRI



† Starting charge does not guarantee line charge. Running pressure must be checked by a technician.

www.mrcool.com